



McIntosh MC754 Power Amplifier

- Power Output:** Stereo: 100 watts across 8 ohms or 4 ohm loads is the minimum sine wave continuous average power output per channel, 20 Hz to 20,000 Hz with both channels operating. Mono (Bridged): 200 watts across an 8 ohm load is the minimum sine wave continuous average power output, 20 Hz to 20,000 Hz.
- Output Load Impedance:** Stereo: 4 ohms or 8 ohms. Mono: 8 ohms; connect across the output of both channels.
- Total Harmonic Distortion:** Stereo: 0.02% maximum harmonic distortion at any power level from 250 milliwatts to rated power per channel, 20 Hz to 20,000 Hz, both channels operating. Mono: 0.02% maximum harmonic distortion at any power level from 250 milliwatts to rated power, 20 Hz to 20,000 Hz.
- Intermodulation Distortion:** Stereo: 0.02% maximum if instantaneous peak power output is 200 watts or less per channel, both channels operating, any combination of frequencies, 20 Hz to 20,000 Hz. Mono: 0.02% maximum if instantaneous peak power output is 400 watts or less, any combination of frequencies, 20 Hz to 20,000 Hz.
- Power Guard:** Clipping is prevented and total harmonic distortion does not exceed 2.0% with up to 20 dB overdrive at 1,000 Hz.
- Size**
13 1/8" (33.3 cm) w, 9 5/8" (24.4 cm) d by, 5 9/16" (14.1 cm) h
- Weight**
21 lbs. (9.5 Kg) net; 25 lbs. (11.3 Kg) in shipping carton